

**TECHNICAL DATA
DATASHEET D0365 REV.-**

SILICON CARBIDE 1200 V / 160 mΩ POWER MOSFET DIE

Applications:

- Solar inverters • Switched-mode power supply • High voltage DC/DC converters
- Battery charges • Motor drives • Pulsed power application

Features:

- High blocking voltage with low on-resistance
- High speed switching with low capacitances
- Easy to parallel and simple to drive
- Avalanche ruggedness
- Resistant to latch-up
- Silver backside metal

Maximum Ratings ($T_A = 25\text{ }^\circ\text{C}$, unless otherwise specified)

Characteristics	Symbol	Conditions	Min.	Typ.	Max.	Units	Note
Drain - Source Voltage	V_{DSmax}	$V_{GS} = 0\text{ V}$, $I_D = 100\text{ }\mu\text{A}$			1200	V	
Gate - Source Voltage (dynamic)	V_{GSmax}	AC ($f > 1\text{ Hz}$)	-10		+25	V	
Gate - Source Voltage (static)	V_{GSop}	Static		-5 / +20		V	[1]
Continuous Drain Current	I_D	$V_{GS} = 20\text{ V}$, $T_C = 25\text{ }^\circ\text{C}$			17	A	
		$V_{GS} = 20\text{ V}$, $T_C = 100\text{ }^\circ\text{C}$			12		
Pulsed Drain Current	$I_{D(pulse)}$	Pulse width t_P limited by T_{Jmax}			40	A	
Operating Junction and Storage Temperature	T_J , T_{stg}				-55 to 175	$^\circ\text{C}$	
Maximum Processing Temperature	T_{Proc}	10 min. maximum			325	$^\circ\text{C}$	

[1] Recommended turn off gate voltage is -5 V. Recommended turn on gate voltage is 20 V. Do not use with $V_{GSon} < 15\text{ V}$.

**TECHNICAL DATA
DATASHEET D0365 REV.-**
Electrical Characteristics (T_A = 25 °C, unless otherwise specified)

Characteristics	Symbol	Conditions	Min.	Typ.	Max.	Units
Drain Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = 100 μA	1200			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 2.5 mA	2	2.8	4	V
		V _{DS} = V _{GS} , I _D = 2.5 mA, T _J = 175 °C		1.9		V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 1200 V, V _{GS} = 0 V		1	100	μA
Gate Source Leakage Current	I _{GSS}	V _{GS} = 20 V, V _{DS} = 0 V		10	250	nA
Drain Source On-State Resistance	R _{DS(on)}	V _{GS} = 20 V, I _D = 10 A		175	196	mΩ
		V _{GS} = 20 V, I _D = 10 A, T _J = 175 °C		300		mΩ
Transconductance	g _{fs}	V _{DS} = 20 V, I _{DS} = 10 A		3.3		S
		V _{DS} = 20 V, I _{DS} = 10 A, T _J = 175 °C		3.4		S
Input Capacitance	C _{ISS}	V _{GS} = 0 V		513		pF
Output Capacitance	C _{OSS}	V _{DS} = 1000 V		35		
Reverse Transfer Capacitance	C _{RSS}	V _{AC} = 25 mV		2		
C _{OSS} Stored Energy	E _{OSS}	f = 1 MHz		20		
Internal Gate Resistance	R _{G(int)}	f = 1 MHz, AC = 25 mV		6		Ω
Gate to Source Charge	Q _{gs}	V _{DS} = 800 V, V _{GS} = -5 / 20 V I _D = 10 A Per IEC60747-8-4 pg 21		7		nC
Gate to Drain Charge	Q _{gd}			8		
Total Gate Charge	Q _g			26		

* Pulse width < 200 μs.

**TECHNICAL DATA
DATASHEET D0365 REV.-**

Reverse Diode Characteristics (T_A = 25 °C, unless otherwise specified)

Characteristics	Symbol	Conditions	Typ.	Max.	Units
Diode Forward Voltage	V _{SD}	V _{GS} = -5 V, I _{SD} = 5 A	3.7		V
	V _{SD}	V _{GS} = -5 V, I _{SD} = 5 A, T _J = 175°C	2.5		V
Reverse Recovery Time	t _{rr}	V _{GS} = -5 V, I _{SD} = 10 A, T _J = 25 °C	6		ns
Reverse Recovery Charge	Q _{rr}	V _R = 800V	40		nC
Peak Reverse Recovery Current	I _{rm}	dif / dt = 2533 A / μs	11		A

Typical Performance

All the graphs are based on a die placed in a TO-247-4 package.




Figure 1. Output Characteristics T_J = -55 °C




Figure 2. Output Characteristics T_J = 25 °C

TECHNICAL DATA
DATASHEET D0365 REV.-




Figure 3. Output Characteristics $T_J = 175^\circ\text{C}$




Figure 4. Normalized On-Resistance vs. Temperature




Figure 5. On-Resistance vs. Drain Current For Various Temperatures




Figure 6. On-Resistance vs. Temperature For Various Gate Voltage




Figure 7. Transfer Characteristic for Various Junction Temperatures




Figure 8. Body Diode Characteristic at $T_J = -55^\circ\text{C}$

TECHNICAL DATA
DATASHEET D0365 REV.-




Figure 9. Body Diode Characteristic at $T_J = 25^\circ\text{C}$




Figure 10. Body Diode Characteristic at $T_J = 175^\circ\text{C}$




Figure 11. Threshold Voltage vs. Temperature




Figure 12. Gate Charge Characteristic




Figure 13. 3rd Quadrant Characteristic at $T_J = -55^\circ\text{C}$




Figure 14. 3rd Quadrant Characteristic at $T_J = 25^\circ\text{C}$

**TECHNICAL DATA
DATASHEET D0365 REV.-**




Figure 15. 3rd Quadrant Characteristic at $T_J = 175\text{ }^\circ\text{C}$




Figure 16. Output Capacitor Stored Energy




Figure 17. Capacitances vs. Drain-Source Voltage (0 - 200 V)




Figure 18. Capacitances vs. Drain-Source Voltage (0 - 1000 V)




Figure 19. Continuous Drain Current Derating vs. Case Temperature




Figure 20. Maximum Power Dissipation Derating vs. Case Temperature

TECHNICAL DATA
DATASHEET D0365 REV.-




Figure 21. Transient Thermal Impedance (Junction - Case)




Figure 22. Safe Operating Area




Figure 23. Clamped Inductive Switching Energy vs. Drain Current ($V_{DD} = 600V$)




Figure 24. Clamped Inductive Switching Energy vs. Drain Current ($V_{DD} = 800V$)




Figure 25. Clamped Inductive Switching Energy vs. $R_{G(ext)}$




Figure 26. Clamped Inductive Switching Energy vs. Temperature

TECHNICAL DATA
DATASHEET D0365 REV.-




Figure 27. Switching Times vs. $R_{G(ext)}$






Figure 28. Switching Times Definition

**TECHNICAL DATA
DATASHEET D0365 REV.-**

Mechanical Dimensions



Parameter	Typical Value	Unit
Die Dimensions (L x W)	Please contact your sales representative to get the detailed information about die layout and dimensions.	mm
Exposed Source Pad Metal Dimensions (L x W) Each		mm
Sense Pad Metal Dimensions (L x W)		mm
Gate Pad Dimensions (L x W)		mm
Top Side Source Metallization (Al)		μm
Top Side Gate Metallization (Al)		μm
Bottom Drain Metallization (Ni / Ag)		μm

TECHNICAL DATA
DATASHEET D0365 REV.-

DISCLAIMER:

1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).

2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.

3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.

4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.

5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.

6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.

7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.