

**TECHNICAL DATA  
DATASHEET D0365 REV.-**

## SILICON CARBIDE 1200 V / 16 mΩ POWER MOSFET DIE

**Applications:**

- Solar inverters • Switched-mode power supply • High voltage DC/DC converters
- Battery charges • Motor drives • Pulsed power application

**Features:**

- High blocking voltage with low on-resistance
- High speed switching with low capacitances
- Easy to parallel and simple to drive
- Avalanche ruggedness
- Resistant to latch-up
- Silver backside metal

**Maximum Ratings ( $T_A = 25\text{ }^\circ\text{C}$ , unless otherwise specified)**

Characteristics	Symbol	Conditions	Min.	Typ.	Max.	Units	Note
Drain - Source Voltage	$V_{DSmax}$	$V_{GS} = 0\text{ V}$ , $I_D = 100\text{ }\mu\text{A}$			1200	V	
Gate - Source Voltage (dynamic)	$V_{GSmax}$	AC ( $f > 1\text{ Hz}$ )	-8		+22	V	
Gate - Source Voltage (static)	$V_{GSop}$	Static		-4 / +18		V	[1]
Continuous Drain Current	$I_D$	$V_{GS} = 18\text{ V}$ , $T_C = 25\text{ }^\circ\text{C}$			120	A	
		$V_{GS} = 18\text{ V}$ , $T_C = 100\text{ }^\circ\text{C}$			85		
Pulsed Drain Current	$I_{D(pulse)}$	Pulse width $t_P$ limited by $T_{Jmax}$			250	A	
Operating Junction and Storage Temperature	$T_J$ , $T_{stg}$				-55 to 175	$^\circ\text{C}$	
Maximum Processing Temperature	$T_{Proc}$	10 min. maximum			325	$^\circ\text{C}$	

[1] Recommended turn off gate voltage is -4 V. Recommended turn on gate voltage is 18 V. Do not use with  $V_{GSon} < 12\text{ V}$ .

**TECHNICAL DATA  
DATASHEET D0365 REV.-**
**Electrical Characteristics (T<sub>A</sub> = 25 °C, unless otherwise specified)**

Characteristics	Symbol	Conditions	Min.	Typ.	Max.	Units
Drain Source Breakdown Voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> = 0 V, I <sub>D</sub> = 100 μA	1200			V
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 30 mA	2	2.5	4	V
		V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 30 mA, T <sub>J</sub> = 175 °C		1.7		V
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> = 1200 V, V <sub>GS</sub> = 0 V		1	100	μA
Gate Source Leakage Current	I <sub>GSS</sub>	V <sub>GS</sub> = 18 V, V <sub>DS</sub> = 0 V		10	250	nA
Drain Source On-State Resistance	R <sub>DS(on)</sub>	V <sub>GS</sub> = 18 V, I <sub>D</sub> = 75 A		16	23	mΩ
		V <sub>GS</sub> = 18 V, I <sub>D</sub> = 75 A, T <sub>J</sub> = 175 °C		25		mΩ
Transconductance	g <sub>fs</sub>	V <sub>DS</sub> = 20 V, I <sub>DS</sub> = 75 A		24		S
		V <sub>DS</sub> = 20 V, I <sub>DS</sub> = 75 A, T <sub>J</sub> = 175 °C		28		S
Input Capacitance	C <sub>ISS</sub>	V <sub>GS</sub> = 0 V		5251		pF
Output Capacitance	C <sub>OSS</sub>	V <sub>DS</sub> = 1000 V		228		
Reverse Transfer Capacitance	C <sub>RSS</sub>	V <sub>AC</sub> = 25 mV		28		
C <sub>OSS</sub> Stored Energy	E <sub>OSS</sub>	f = 1 MHz		134		
Internal Gate Resistance	R <sub>G(int)</sub>	f = 1 MHz, AC = 25 mV		1.6		Ω
Gate to Source Charge	Q <sub>gs</sub>	V <sub>DS</sub> = 800 V, V <sub>GS</sub> = -4 / 18 V I <sub>D</sub> = 40 A Per IEC60747-8-4 pg 21		161		nC
Gate to Drain Charge	Q <sub>gd</sub>			63		
Total Gate Charge	Q <sub>g</sub>			287		

\* Pulse width < 200 μs.

**TECHNICAL DATA  
DATASHEET D0365 REV.-**

**Reverse Diode Characteristics ( $T_A = 25\text{ }^\circ\text{C}$ , unless otherwise specified)**

Characteristics	Symbol	Conditions	Typ.	Max.	Units
Diode Forward Voltage	$V_{SD}$	$V_{GS} = -4\text{ V}, I_{SD} = 37.5\text{ A}$	4.0		V
	$V_{SD}$	$V_{GS} = -4\text{ V}, I_{SD} = 37.5\text{ A}, T_J = 175^\circ\text{C}$	3.5		V
Reverse Recovery Time	$t_{rr}$	$V_{GS} = -4\text{ V}, I_{SD} = 75\text{ A}, T_J = 25\text{ }^\circ\text{C}$	26		ns
Reverse Recovery Charge	$Q_{rr}$	$V_R = 800\text{V}$	322		nC
Peak Reverse Recovery Current	$I_{rmm}$	$di/dt = 2500\text{ A}/\mu\text{s}$	19		A

**Typical Performance**

All the graphs are based on a die placed in a TO-247-4 package.




Figure 1. Output Characteristics  $T_J = -55\text{ }^\circ\text{C}$




Figure 2. Output Characteristics  $T_J = 25\text{ }^\circ\text{C}$

**TECHNICAL DATA**  
**DATASHEET D0365 REV.-**




Figure 3. Output Characteristics  $T_J = 175\text{ }^\circ\text{C}$




Figure 4. Normalized On-Resistance vs. Temperature




Figure 5. On-Resistance vs. Drain Current For Various Temperatures




Figure 6. On-Resistance vs. Temperature For Various Gate Voltage




Figure 7. Transfer Characteristic for Various Junction Temperatures




Figure 8. Body Diode Characteristic at  $T_J = -55\text{ }^\circ\text{C}$

**TECHNICAL DATA**  
**DATASHEET D0365 REV.-**




Figure 9. Body Diode Characteristic at  $T_J = 25\text{ }^\circ\text{C}$




Figure 10. Body Diode Characteristic at  $T_J = 175\text{ }^\circ\text{C}$




Figure 11. Threshold Voltage vs. Temperature






Figure 12. Gate Charge Characteristic



**TECHNICAL DATA**  
**DATASHEET D0365 REV.-**

Figure 13. 3rd Quadrant Characteristic at  $T_J = -55\text{ }^\circ\text{C}$




Figure 15. 3rd Quadrant Characteristic at  $T_J = 175\text{ }^\circ\text{C}$




Figure 17. Capacitances vs. Drain-Source Voltage (0 - 200 V)





Figure 18. Output Capacitor Stored Energy






Figure 18. Capacitances vs. Drain-Source Voltage (0 - 1000 V)




**TECHNICAL DATA**  
**DATASHEET D0365 REV.-**

**Figure 19. Continuous Drain Current Derating vs. Case Temperature**




**Figure 21. Transient Thermal Impedance (Junction - Case)**




**Figure 23. Clamped Inductive Switching Energy vs. Drain Current ( $V_{DD} = 600V$ )**



**Figure 20. Maximum Power Dissipation Derating vs. Case Temperature**



**Figure 22. Safe Operating Area**




**Figure 24. Clamped Inductive Switching Energy vs. Drain Current ( $V_{DD} = 800V$ )**




**TECHNICAL DATA  
DATASHEET D0365 REV.-**

**Figure 25. Clamped Inductive Switching Energy vs.  $R_{G(ext)}$**



**Figure 27. Switching Times vs.  $R_{G(ext)}$**

**Figure 26. Clamped Inductive Switching Energy vs. Temperature**





**Figure 28. Switching Times Definition**



**TECHNICAL DATA**  
**DATASHEET D0365 REV.-**

**Mechanical Dimensions**



Parameter	Typical Value	Unit
Die Dimensions (L x W)	Please contact your sales representative to get the detailed information about die layout and dimensions.	mm
Exposed Source Pad Metal Dimensions (L x W) Each		mm
Sense Pad Metal Dimensions (L x W)		mm
Gate Pad Dimensions (L x W)		mm
Top Side Source Metallization (Al)		μm
Top Side Gate Metallization (Al)		μm
Bottom Drain Metallization (Ni / Ag)		μm

---

**TECHNICAL DATA**  
**DATASHEET D0365 REV.-**

**DISCLAIMER:**

1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).

2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.

3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.

4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.

5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.

6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.

7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.